

OpenScape Xpressions V7

Connection

Connection to	<ul style="list-style-type: none"> • HiPath 3000 from V6 with CorNet-IP/T.38 • HiPath 4000 from V3 with CorNet-IP/T.38 • HiPath 4000 from V6 with SIP/T.38 • OpenScape Voice from V3.1 with SIP/T.38 • HiPath DX with CorNet NQ • Hicom 150 E/H with functionality of Xpressions V4.0 • Hicom 300 E/H with functionality of Xpressions V4.0 • HiPath 3000 before V5 with functionality of Xpressions V4.0 • HiPath 3000 V5 with functionality of Xpressions V5 • HiPath 4000 V1 with functionality of Xpressions V4.0 • HiPath 4000 V2 with functionality of Xpressions V5 • HiPath 8000 before 2.2 with functionality of Xpressions V4 • HiPath 8000 V3 with functionality of Xpressions V5 • Project specific, other PBX (DSS1/QSIG) • Customer LAN (TCP/IP) (100 BaseT) <p>Project specific released are these connectivities:</p> <ul style="list-style-type: none"> • Cisco UC Manager 6, 7, 8, 8.6, 9 (SIP) • Alcatel OmniPCX Enterprise 7, 8, 9, 9.1, 10, 10.1 (ISDN)
Number of channels per server/distributed system at Hicom 300 / HiPath 4000	Up to 60 / 300 channels / ports, of which <ul style="list-style-type: none"> • Max. 60 / 300 Voice • Max. 60 / 300 Fax
Number of channels per server to HiPath 3000	Up to 60 channels / ports, of which <ul style="list-style-type: none"> • Max. 60 voice • Max. 60 fax
Number of channels per server using IP-connectivity (G.711) For G.729	HiPath 4000: max. 40 channels per PC / max. 280 per distributed system OpenScape Voice: max. 60 channels per PC / max. 300 per distributed system max. 40 channels per PC / max. 280 per distributed system
Number of channels for audio conferencing	150-200 channels when using 8 core computers
Number of channels for web conferencing	Max. 200, of which 100 in a single web conference
Access to user mailbox	
Telephone access to	<ul style="list-style-type: none"> • Voicemail • fax mail • E-mail
PC client access to	<ul style="list-style-type: none"> • Voicemail • fax mail • E-mail
Supported services	
Supported desktop clients	<ul style="list-style-type: none"> • Netscape Communicator 7.1 • Web Client Internet Explorer 7.0, 8.0 and 9,Firefox 2.0 to 3.6 • Web AssistantInternet Explorer 7.0, 8.0 and 9,Firefox 16.0.1, Safari 5.1.7 • Microsoft Outlook XP/2003/2007/2010 • Microsoft Outlook Express V5.5 or higher • OpenScape Xpressions Communications Client • OpenScape Xpressions Web Assistant
E-mail integration with Microsoft Exchange	<ul style="list-style-type: none"> • Microsoft Exchange 2003/2007/2010
E-mail integration with Lotus Notes / Domino	<ul style="list-style-type: none"> • Lotus Notes/Domino 6.5.1/6.5.3/6.5.4 • Lotus Notes/Domino 7.0/7.0.1/7.0.2 • Lotus Notes 8.0.X/8.5.0/8.5.1/8.5.2/8.5.3

OpenScape Xpressions V7	
E-mail gateways	<ul style="list-style-type: none"> • SAP R/3 from 4.5b via SAPconnect • SMTP mail
Directory integration via LDAP Connector	Customer Directory
SMS (Short Message Service)	
SMS message to mobile telephone on arrival of new message or via mail client	GSM 900/1800 networks
Max. number of characters to be transmitted (including special characters)	Max. 160 characters
Number of messages per SMS box	Approx. 300 per hour
Number of SMS boxes per OpenScape Xpressions V5	Max. 2
Fax services	
Fax services	Fax G3
Fax coding in accordance with T.30	Yes
Fax coding in accordance with T.38	Yes
Fax-on-demand	Yes
Access protection	
Mandatory password	Yes
Min. number of characters in the personal password	1
Max. number of characters in the personal password	24
Configuration sizes	
Max. number of users / mailboxes E-mail in case of replication Voicemail Unified Messaging (voice mail, fax mail, SMS)	Primergy / Distributed System 600 4.000 /20.000 2.000 /10.000
Max. number of messages per user	Dependent on HDD, not strictly limited
Max. message memory per mailbox	Dependent on HDD, not strictly limited
User languages on telephone and display	German, English (UK), English (US), French, French (Canada), Italian, Spanish, Spanish (US), Dutch, Portuguese, Portuguese (Brazil), Turkish, Russian, Japanese
Max. number of individual distribution lists per user	99
Max. number of addresses per distribution list	99
Max. number of announcements per user	9
Hardware requirements PC server min. equipment	
Processor (Intel only)	Standard: Intel Pentium IV 2 GHz High End: Intel Pentium IV > 2 GHz
RAM	Minimum/Standard: 2 GB / 4 GB + 128 MB for >2p + 128 MB for Exchange + 1 GB for TTS + 100 MB per installed voice + 2.048 MB for audio conferencing + 1.048 MB for OpenScape Web Client High End: > 4 GB
Hard disk (for 4 GB or more with 1 GB FAT, rest NTFS) Additional hard disk for data backup	Minimum: 4 GByte (in the event of upgrading) Standard: 2 x 100 GByte (IDE or SCSI) High End: n x 9/18/36/72 GByte (RAID5)
LAN card	Ethernet (10BT)/100BT
V.24 / COM port	Additional V.24 board possibly necessary from 2nd COM (service modem, if necessary MWI modem)
PCI/PCIe slots (for voice/fax interface boards)	Minimum: 1 Maximum: 5

OpenScape Xpressions V7	
Operating system (64-bit)	<ul style="list-style-type: none"> • Windows 7 Professional • Windows Server 2003 R2 SP2 Enterprise • Windows Server 2008 Standard or Enterprise
Hardware requirements – PC client	
Processor	Minimum: <ul style="list-style-type: none"> • Windows XP : Pentium IV 1,300 MHz • Windows Vista/7: according to the producer's recommendation • Windows Server 2003 and 2008 (terminal server): according to the producer's recommendation Recommended: >= 3.0 GHz
RAM	Minimum: 512 MByte Recommended: >= 1.024 MByte
LAN card	Ethernet 10BT/100BT
Operating system (recommended)	<ul style="list-style-type: none"> • Windows XP Professional from SP2 • Windows Vista Business or Enterprise • Windows 7 Professional/Ultimate/Enterprise Edition
Microsoft Outlook (recommended)	<ul style="list-style-type: none"> • Outlook XP SP2 • Outlook 2003 • Outlook 2007 • Outlook 2010
Lotus Notes,	<ul style="list-style-type: none"> • Lotus Notes 6.5.x • Lotus Notes 7.0.x • Lotus Notes 8.0 / 8.0.1 • Lotus Notes 8.5.0/8.5.1/8.5.2/8.5.3
Optional accessories	<ul style="list-style-type: none"> • Sound card • Microphone • Headphones

Copyright © Unify GmbH & Co. KG 10/2013
 Hofmannstr. 51, 81379 Munich/Germany

All rights reserved.

Reference No.: A31002-S2370-D100-3-7629

The information provided in this document contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.

Availability and technical specifications are subject to change without notice.

Unify, OpenScape, OpenStage and HiPath are registered trademarks of Unify GmbH & Co. KG. All other company, brand, product and service names are trademarks or registered trademarks of their respective holders.